





The presentation that follows lists only one combination of parts. Obviously the clinical situation may call for substitution of another part on this slide




	Size	Part #
( Oneside	Torque/Ratchet Wrench	TR-900-01
B	Thumbwheel/ITI Wrench Adapter	ITI-Adapter
	.048 Hex Driver short	SDS048
<u> </u>	.048 Hex Driver long	SDL048
	Insert Placement/Removal Instrument	TFSU

Prosthetic instruments needed




Assemble screw driver with ITI - Adapter (thumb-wheel / adapter) Insert assembled screw driver into cover screw and turn counter clockwise


Remove cover screw from implants





Insert the abutment into the One Stage Implant and rotate clockwise until snug







When the overdenture abutment is screwed into the implant at 30-35 Ncm the Morse taper will lock the abutment in place.


Two abutments in place

100

Put silicon blockout ring on the abutment







Remove enough material form the tissue side of the denture to ensure that it does not interfere with the super snap.

Typically it is necessary to make the cavity in the denture 2-3mm wider and 1-2mm taller than the super snap

**Blue Sky Bio** 

Insert denture and ensure that when it is fully seated it does not touch the super snap

<u>k</u>.

Insert resin of choice into the cavities in the denture

**Blue Sky Bio** 

Insert denture again over the housings and with the patient occluding on the denture

1



Let resin cure with denture in appropriate occlustion

**Blue Sky Bio** 

Void Excess resin

Void

Remove denture from mouth and fill any voids with resin. Trim any excess resin around the housing and on the ridge area

Finished prosthesis with inserts in place

Remove the insert you want to change with the sharp point of the removal instrument

**Blue Sky Bio** 

Place the insert with the desired retention into the denture with the opposite side of the removal instrument